

PAPER NAME	AUTHOR		
Jurnal Bu Silvi 4.docx	Nurul Amalia Silviyanti Siswoyo		
WORD COUNT	CHARACTER COUNT		
2679 Words	13458 Characters		
PAGE COUNT	FILE SIZE		
6 Pages	262.3KB		
SUBMISSION DATE	REPORT DATE		
Mar 16, 2024 8:43 AM GMT+7	Mar 16, 2024 8:43 AM GMT+7		

• 9% Overall Similarity

The combined total of all matches, including overlapping sources, for each database.

- 8% Internet database
- Crossref database

- 2% Publications database
- Crossref Posted Content database

• Excluded from Similarity Report

Manually excluded sources

• Manually excluded text blocks

Comparative study of two different reflectors, zincalume steel and aluminum foil tape in the application of solar cookers

Nurul Amalia Silviyanti S¹, Santoso¹

¹Faculty of Agriculture, University of Abdurachman Saleh, Situbondo, East Java Indonesia.

Email: nurul amalia silvi@unars.ac.id

Abstract. The amount of energy resource from fossil continue to decrease, these lead to high demand for renewable energy. One of the biggest energy resources in our nature is solar power. A solar cooker is a device that used solar power to cooked a meal. The performance and temperature of solar cookers depend on the material we used in device. One of the most important components in solar cooking is reflector because solar cookers used a mirrored reflector to collect and transfer sun rays into the cooking pot to increase the temperature inside the pot. These paper compare two different material as a reflector in solar cookers. The first reflector is aluminum foil tape, these materials very cheap, light, easy to use so it could be applied in many designs. The Second reflector used was zincalume steel, it has the highest reflector among other thin steel available in the market. The design of panel reflector from aluminum foil tape was 4 rectangular and the design of zincalume steel reflector similar to cone. The performance of two different reflectors has been analyzed in Solar cookers used to boil 500ml water for 120 minutes. Water temperature from the first and the second reflector showed a similar result. It showed that reflector made from aluminum foil tape and zincalume steel has similar reflectivity.

Key word : Solar cookers, Reflector, Renewable Energy

1. Introduction

In Indonesia, many households use petroleum gas as the main fuel to cook, but the gas came from fossils which in danger of extinction. Moreover burning petroleum gas produces carbon dioxide as known as a greenhouse gas which is the main element to contributes to global warming. Therefore we must use the new energy resource to replace fossil fules[1]. The most powerful and free energy in our nature is sunray. Many researchers already used sunray as renewable energy. Indonesia placed in the equator, thus it can get enough sunray through the year with average power radiation of 4.8 kWh/m² for 8-10 hour per day[2][3].

The utilization of solar power to replace petroleum gas was to cook with solar cookers. Solar cookers are the device used sunray as fuel to cooked the meal[4]. Jolar cookers use free energy from the sun, so it's cheaper and clean because it didn't release carbondioxide[5]. Despite the low cost and clean state, solar cookers used a longer time to cooked than conventional cookers[6]. In many developed countries such as Indonesia, people still reluctant to used solar cooking due to the long time to cooked and the strong radiant from the sunray which made it uncomfortable to cook.

This paper tried to make a solar cooker with a design to avoid strong radiant so that people can more comfortable using it. Instead of using a common design with direct and reflected sunlight, these cookers used a trapezium reflector to guide the sunray into the base of the cooking tray. Without the direct sunlight and the cover above the cooking tray, the user of solar cookers can cook with more ease because the reflected sunray (which usually give a strong dazzled to the eyes) transfer directly under the cooking tray[7]. Another object analyzed in this paper is the reflector panel. One of the most important components in solar cooking is the reflector because solar cookers used a mirrored reflector to collect and transfer sun rays into the cooking pot to increase the temperature inside the pot. These paper compare two different material as a reflector in solar cookers to get the best yet cheap material for solar cookers.

2. Principle of Solar Cookers

solar cooker is a device to convert sunray into heat then used to cook the meal in the tray/pot[8]. These devices used a concentrator or reflector to collect sunray and transfer direct/indirectly into the cooking pot[9]. There are many types of solar cookers, based on concentrating/reflector there are three categories which the most popular and used widely. As we can see in fig.1, the three solar cookers are solar cookers box type, panel type and parabolic type[10]. Solar cooker box type has a similar design with oven, mostly had the rectangular type with or without addition reflector panel. Solar cooker panel types almost similar to box type, but it came with more various designs (not always rectangular) and there is an addition of panel reflectors to enhance the performance of solar cooker. Parabolic solar cooker mostly used parabolic panel and put the cooking pot right on top of it.



Among these three, parabolic solar cooker showed the highest temperature, but the design of parabolic solar cookers make it difficult for the user because of strong radiant. Meanwhile, box type and panel solar cooker perform lower temperature than parabolic type, but user friendly because the radiant not as strong as in parabolic type. Therefore people prefer used box type or panel solar cooker to used daily in their household. Apart from the shape of the reflector, the material used as a reflector and the shape of the reflector (inclined wavy or flat plate) play an important role in order to reach good performance in solar cookers[12]. Hence in this paper, we used two different reflectors from two different materials with a slightly different shape but a similarly large area.

3. Design and Method

3.1. Design

The solar cooker is made from wood and all the skin on the surface is painted black to absorb more heat (see fig.2). The design of these solar cookers inspired by [7] with the same purpose, to create a low-cost solar cooker with high performance and easy to use. These devices used two different reflectors, the reflector panel design like Prisma trapezium (as seen in fig.2b) with two big rectangular 4620 cm², two rectangular 2310 cm² and four triangular 1155 cm². The panel reflector is made from

thin wood and coated with aluminum tape. The second reflector used zincalume (alloy of 55% aluminum and 45% zinc) with a design similar to cone but without the top. The half-cylinder reflector employ as a connector from the reflector panel and cooking tray and used to reflect the sunray from the panel reflector into the tray. The cooking tray is made from stainless steel with the bottom tray paint tint black to prevent the reflection from stainless steel and to absorb more heat.



Figure 2. Solar Cooker, a). Figure from side, b). Figure from above, c). Up front of solar cooker with mirror cover lid

One of the factors for solar cookers to reach high temperature is heat loose such as used the lid to prevent evaporation from the cooking tray. The lid (see fig.2c) used in this device is made from a mirror with a size of 30 x 60 cm to cover the tray. Even though Indonesia gets enough sunshine all year, but the sun has its own move. The sun's move from west to the east make it difficult to track the ray source for these solar cookers. The device design to be used in a household with limited sunray due to many barriers such as a wall or trees. Therefore these solar cookers are given four wheels, thus it can easily be moved around to find a better angle and place for more sunray. This paper design with the purpose to make the user can be cooked more convenient, thus the panel reflector not directed to the cooking user. Instead, the user got in the shadow from the panel reflector and did not get direct strong radiation from the sunray.

3.2. Experimental Set Up

The experiment was already done in the backyard to represent real-life with many trees and the surrounding wall. The solar cooker used to heat water for 120 minutes between 09.00 am and 11.00 am. Power radiation of sunray and temperature of the water had been collected manually every 5 minutes. The device to measure radiation was lux meter to and solar power meter, meanwhile infrared thermometer gun has been used to measure temperature in water. The size of the cooking tray used in this experiment is 31 x 25 cm, the tray fills with 500 ml water. There is only one kind of solar cooker used in this experiment, thus the performance of reflector panels with aluminum and zincalume has been measured on a different day. After solar cookers with reflector panel with aluminum tape has been measured, the panel replaced with cone panel from zincalume. The data collect many times to get the humidity, radiation and temperature surrounding as similar as for those two reflector panels.

4. Result and Discussion

The first reflector to evaluated was a reflector based on aluminum tape. The shape similar to trapezium in hope, the angle between the plane can trap and reflect more sunray. From the result (see 4g 3.), the highest temperature perform by aluminum tape reflector was 75.9°C. Meanwhile, the reflector made from zincalume got 72°C as maximum temperature. The result showed that reflector based on aluminum tape perform better than reflector based made from zincalume.



Figure 3. comparative perform of two reflector, aluminum tape and zinalume.

From table 1, we can see solar radiation and illumination when the experiment happen. Even though the two data collect on a different day, the number of solar radiation and illumination show similarity. It is safe to say the two reflectors were analyzed in the same condition. In table 1, we can see that the stronger radiation temperature of water increases faster. When the radiation gets weaker, the temperature inside the water increase slowly it happens because there is a lack of heat absorbance in these devices[13]. When solar radiation not too strong, with the help of solar absorbance the previous heat can be stored safely so that when the heat from the sunray gets weaker there is still the heat from storage to back up so that the temperature does not decrease. On top of that, the experiment only allows taking data until 120 minutes because above 11.00 am the sun changes its position, and with many trees and walls between it is hard to get the maximum amount of the sunray. Moreover, when water reaches the temperature higher than 80°C, the temperature tend to decrease because of different temperature between lid and water made different heat transfer coefficient decrease, it made calor in water decrease too[14].

 Table 1. Performance aluminum tape and zincalume as reflector with solar radiation

Time	Lux	Solar Radiation	Aluminum	Zincalume	Solar Radiation	Lux
(Minutes)		(W/m^2)	Tape (°C)	(°C)	(W/m^2)	
0	154.7	1096	27.6	27.8	897	148.6
10	150.9	1172.7	35	40.5	1020.9	155.2
20	144.7	1191.5	40	48.7	1132.4	153.1
30	152.6	1097.3	48.8	51.3	1029.8	150.7
40	145.5	1052.4	53.5	56.5	939.3	149.5
50	147.2	1211	58.7	58	1007.9	150.2
60	149.7	1081.2	64.8	59.3	1064.5	155.1
70	143.3	1079.3	68.2	60.4	987.4	151.4
80	150.7	1132.8	70.4	62	1079.2	153.2
90	155.6	1018	72.7	68.7	1056.9	145.4
100	151.4	1099.6	73.2	70	1107.3	152.1
110	148.9	1067.5	74.5	71.6	1098.6	147.6
120	145.8	1126.5	75.9	72	1166.2	152.1

Cooking power and efficiency from this device can be calculated using questions 1 and 2[15]. With P is cooking power in W, is a range of temperature, t is time to heated the water, is mass of water (in this case the mass of water is 0.5 kg), is water heat capacity, I is solar radiation and A is heat absorber area.

$$P = \frac{\Delta T}{t} \cdot m_{a.} C_{a.} \tag{1}$$

From question 1, we can see that the solar cooker with a reflector from Aluminum Tape got 14.08 W cooking power. Meanwhile, cooking power with a reflector from Zincalume got 12.89 W.

$$\eta = \frac{P}{I_T A_c} x \, 100\% \tag{2}$$

The efficiency solar cooker calculated with question 2 for reflector Aluminum Tape is 16.37 % and for reflector Zincalume is 14.89 %. The cooking power and efficiency from reflector Aluminum tape higher than reflector Zincalume, although the cooking power from these result tends to lower than regular box type solar cooker [16][17]. Therefore the device needs many improvements to get better performance. The design has been successfully made the user cooking get less radiation, hence it made the cooking activity safer. Therefore the space from by connector made so much space, thus it caused much heat loss.

5. Conclusion

The comparative study of two different reflectors has been investigated. Reflective panel from thin wood coated with aluminum tape and trapezium design got higher temperature than reflective panel from zincalume with half cone design. Maximum temperature reaches 75.9 °C for aluminum tape reflector and zincalume reflector reaches maximum temperature 72°C. The device needs many improvements to get a better performance such as the addition of a heat isolator and heat absorber to prevent heat loss so that it can enhance the temperature more quickly.

References

- S. Indora and T. C. Kandpal. Institutional and community solar cooking in India using SK-23 and Scheffler solar cookers: A financial appraisal. *Renewable Energy*, vol. 120, pp. 501–511, May 2018.
- [2] Abdul Muin, Rita Maria, and Iskandar Bail. Perancangan kompor surya serbaguna dengan susunan absober yang bervariasi. *Jurnal Desiminasi Teknologi*, vol. 5, no. 1, Jan. 2017.
- [3] T. Y. Yanuartanto. Kompor surya menggunakan penyimpan panas dengan variasi ketinggian kompor. skripsi, Sanata Dharma University, 2010.
- [4] Sunil Indora and Tara C Kandpal. Institutional cooking with solar energy: A review. *Renewable and Sustainable Energy Reviews*, vol. 84, pp. 131–154, Mar. 2018.
- [5] Mohammad Aramesh, Mehdi Ghalebani, Alibakhsah Kasaeian, Hosein Zamani, Giulio Loerenzini, Omid Mahian, and Somchai Wongwises. A review of recent advances in solar cooking technology. *Renewable Energy*, vol. 140, pp. 419–435, Sep. 2019.
- [6] Pia Piroschka Otte. Warming Up to Solar Cooking A Comparative Study on Motivations and the Adoption of Institutional Solar Cookers in Developing Countries. *Energy Procedia*, vol. 57, pp. 1632–1641, Jan. 2014.
- [7] Ian Edmond. Low cost realisation of a high temperature solar cooker. *Renewable Energy*, vol. 121, pp. 94–101, Jun. 2018.
- [8] Ishan Purohit. Testing of solar cookers and evaluation of instrumentation error. *Renewable Energy*, vol. 35, no. 9, pp. 2053–2064, Sep. 2010.
- [9] H. Terres, A. Lizardi, S. Chávez, R. López, and M. Vaca. Evaluation of the cooking power in three different solar cookers box-type. *J. Phys.: Conf. Ser.*, vol. 792, p. 012013, Jan. 2017.
- [10] M. Mussard. A solar concentrator with heat storage and self-circulating liquid. Norges teknisk-

naturvitenskapelige universitet, Fakultet for ingeniørvitenskap og teknologi, Institutt for energi- og prosessteknikk, 2013.

- [11] Yunsheng Zhao, Hongfei Zheng, Boyang Sun, Chenji Li, and Yin Wu. Development and performance studies of a novel portable solar cooker using a curved Fresnel lens concentrator. *Solar Energy*, vol. 174, pp. 263–272, Nov. 2018.
- [12] H. Ambarita. Numerical study on the effect of configuration of a simple box solar cooker for boiling water. *IOP Conf. Ser.: Mater. Sci. Eng.*, vol. 308, p. 012028, Feb. 2018.
- [13] Maxime Mussard, Alexandre Gueno, and Ole Jorgen Nydal. Experimental study of solar cooking using heat storage in comparison with direct heating. *Solar Energy*, vol. 98, pp. 375–383, Dec. 2013.
- [14] S. Mahavar, P. Rajawat, R. C. Punia, N. Sengar, and P. Dashora. Evaluating the optimum load range for box-type solar cookers. *Renewable Energy*, vol. 74, pp. 187–194, Feb. 2015.
- [15] A. Muin, R. M. Veranika, and I. Badil. Perancangan kompor surya serbaguna dengan susunan absober yang bervariasi. *Jurnal desiminasi teknologi*, vol. 5, no. 1, Jan. 2017.
- [16] P. J. Lahkar and S. K. Samdarshi. A review of the thermal performance parameters of box type solar cookers and identification of their correlations. *Renewable and Sustainable Energy Reviews*, vol. 14, no. 6, pp. 1615–1621, Aug. 2010.
- [17] F. Yettou, B. Azoui, A. Malek, A. Gama, and N. L. Panwar. Solar cooker realizations in actual use: An overview. *Renewable and Sustainable Energy Reviews*, vol. 37, pp. 288–306, Sep. 2014.

turnitin

• 9% Overall Similarity

Top sources found in the following databases:

- 8% Internet database
- Crossref database

- 2% Publications database
- Crossref Posted Content database

TOP SOURCES

The sources with the highest number of matches within the submission. Overlapping sources will not be displayed.

researchgate.net Internet	6%
docplayer.net Internet	<19
ijetsr.com Internet	<19
krishi.icar.gov.in Internet	<15
S Nurul Amalia Silviyanti, Santoso. "Performance inve Crossref	stigation of conv <19
Talal K Kassem,, M. S Youssef,. "SOLAR COOKERS AN	D ITS APPLICATI
Crossref	
Crossref iptek.its.ac.id Internet	<1%

2%



• Manually excluded sources

Manually excluded text blocks

EXCLUDED SOURCES

S Nurul Amalia Silviyanti,	Santoso.	"Comparative study of two different reflec 65	;%
Overent			

Crossref

iopscience.iop.org

Internet

EXCLUDED TEXT BLOCKS

Indora and T. C. Kandpal. Institutional and community solar cooking in India using ...

Manjula Devi Murugesan, Joseph Daniel, Jayasivakami Balakrishnan. "Simulation study of a box type solar c...

Abdul Muin, Rita Maria

www.univ-tridinanti.ac.id

Jurnal Desiminasi Teknologi

www.univ-tridinanti.ac.id

T. Y. Yanuartanto. Kompor surya menggunakan penyimpan panas dengan variasi k...

iptek.its.ac.id

Sunil Indora and Tara C Kandpal. Institutional cooking with solar energy: A review. ... S Nurul Amalia Silviyanti, Santoso. "Performance investigation of convex lens as light collector in low cost s...

Mohammad Aramesh, Mehdi Ghalebani, Alibakhsah Kasaeian, Hosein Zamani, Giul...

S Nurul Amalia Silviyanti, Santoso. "Performance investigation of convex lens as light collector in low cost s...

Otte. Warming Up to Solar Cooking – A Comparative Study on Motivations and the...

Manjula Devi Murugesan, Joseph Daniel, Jayasivakami Balakrishnan. "Simulation study of a box type solar c...



Ian Edmond. Low cost realisation of a high temperature solar cooker. Renewable E...

iptek.its.ac.id

8] Ishan Purohit. Testing of solar cookers and evaluation of instrumentation error. ...

S Nurul Amalia Silviyanti, Santoso. "Performance investigation of convex lens as light collector in low cost s...

A. Lizardi, S. Chávez, R. López, and M. Vaca. Evaluation of the cooking power in thr... www.ijrte.org

M. Mussard. A solar concentrator with heat storage and self-circulating liquid

Vednath P. Kalbande, Pramod V. Walke, Sachin Untawale, Man Mohan. "Performance evaluation of novel he...

J. Phys

www.ijrte.org

Norges teknisk-naturvitenskapelige universitet, Fakultet for ingeniørvitenskap og t... nbi.ku.dk

Yunsheng Zhao, Hongfei Zheng, Boyang Sun, Chenji Li, and Yin Wu. Development a... iptek.its.ac.id

H. Ambarita. Numerical study on the effect of configuration of a simple box solar c...

www.proceedings.com

IOP Conf. Ser.: Mater. Sci. Eng., vol. 308, p

www.ej-eng.org

Maxime Mussard, Alexandre Gueno

ia601700.us.archive.org

vol

www.hindawi.com

Mahavar, P. Rajawat, R. C. Punia, N. Sengar

www.jetir.org



Perancangan kompor surya serbaguna dengan susunanabsober yang bervariasi. J...

sinta3.ristekdikti.go.id

P. J. Lahkar and S. K. Samdarshi. A review of the thermal performance parameters...

books.aijr.org

F. Yettou, B. Azoui, A. Malek, A. Gama, and N. L. Panwar. Solar cooker realizations ... ir.uiowa.edu

Comparative study of two different reflectors, zincalume steeland aluminum foil ta... nlist.inflibnet.ac.in

Agriculture, University of Abdurachman Saleh, Situbondo

A D Pahlewi, C Handayani. "Temperature and Salinity Condition Based on Field Measurement at Pasir Putih ...

The amount of energy

www.researchgate.net

East Java

S Nurul Amalia Silviyanti, Santoso. "Performance investigation of convex lens as light collector in low cost s...